Now Includes: 5 Year Parts & Lightning Protection Warranty SURVIVOR® ATV

Fully Electronic Portable Flattop - Steel Deck

STANDARD FEATURES

- Three standard widths: 10ft, 11ft and 12ft (available up to 14ft, NTEP Certified)
- 75,000 lb load cells and pre-assembled G-Force[™] mounts
- Up to 270,000 lb full scale capacity
- Top access for electronics
- NTEP Certified, CC 02-003A2
- 100,000lb Concentrated Load Capacity (CLC)
- 100,000 lb Dual Tandem Axle (DTA)
- Bolt-on backfill ramp bulkheads (removable for concrete approaches)
- End clean out
- Span deflection ratio (1:1200) for legal highway loads

Package includes: Bolt-on backfill ramp bulkheads (removable for concrete approaches); assembled weighbridge modules and weighbridge fasteners; load cells with conduit fitting; load cell mounts; copper transient bypass cables at each load cell; metal conduit on weighbridge for load cell cable runs; polycoated flexible steel conduit from load cell to metal conduit; conduit fittings from poly-coated flexible steel to metal conduit; FRP junction box(es); homerun cable to indicator (60ft long) and print packages including installation manual.

Package does not include: Indicator; printer; freight charges including material handling; shipping charges, transportation permits and fees, escort(s) charge, and insurance transportation fees.














SPECIFICATIONS

LOAD CELLS AND MOUNT ASSEMBLIES:

75,000 lb capacity; G-Force™ Patented Self-Checking Mounting System, top access to load cells

FULL SCALE CAPACITY:

Up to 270,000 lb

DEFLECTION RATIO:

1:1200

CONCENTRATED LOAD CAPACITY (CLC):

100,000 lb

DUAL TANDEM AXLE (DTA):

100,000 lb

APPROVALS:

NTEP Certified per H-44, Class IIIL, CC 02-003A2

WARRANTY:

Five-year limited warranty on the weighbridge Five-year parts warranty, including lightning protection

Please refer to Warranty Statements starting on page 53

DUE TO THE VARIETY OF CONFIGURATIONS, PLEASE CONSULT THE FACTORY TO DISCUSS APPLICATION REQUIREMENTS AND FOR COMPLETE SPECIFICATIONS AND PRICE QUOTATIONS.